



**Hewlett Packard**  
Enterprise

# HPE Security ArcSight Connectors

SmartConnector for Windows Event Log –  
Unified: Microsoft WINS Server

Supplemental Configuration Guide

March 29, 2013

## Supplemental Configuration Guide

### SmartConnector for Windows Event Log – Unified: Microsoft WINS Server

March 29, 2013

Copyright © 2010 – 2013 Hewlett Packard Enterprise Development LP

#### Warranty

The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise Development LP shall not be liable for technical or editorial omissions contained herein. The information contained herein is subject to change without notice. The network information used in the examples in this document (including IP addresses and hostnames) is for illustration purposes only. Hewlett Packard Enterprise Development LP products are highly flexible and function as you configure them. The accessibility, integrity, and confidentiality of your data is your responsibility. Implement a comprehensive security strategy and follow good security practices. This document is confidential.

#### Restricted Rights Legend

Confidential computer software. Valid license from Hewlett Packard Enterprise Development LP required for possession, use or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

Follow this link to see a complete statement of Hewlett Packard Enterprise Development LP copyrights, trademarks and acknowledgements:

<https://www.protect724.hpe.com/docs/DOC-13026>.

## Revision History

---

Date	Description
03/29/2013	First edition of this guide.

---

## Contents

Product Overview.....	4
WINS Configuration .....	4
Connector Installation and Configuration .....	4
Collect Events from the Application or System Event Log .....	5
Windows 2012/Windows 8 .....	5
General .....	5
4097 .....	5
4098 .....	5
4143 .....	6
4178 .....	6
4179 .....	6
4180 .....	6
4224 .....	6
4318 .....	6
4329 .....	6
4330 .....	6
5001 .....	7
5002 .....	7
4181 .....	7
4252 .....	7
4253 .....	7
4309 .....	7
4325 .....	7
4326 .....	8
4119 .....	8
4337 .....	8

## SmartConnector for Windows Event Log – Unified: Microsoft WINS Server

This guide provides information about the SmartConnector for Windows Event Log – Unified: Microsoft WINS Server and its event mappings to ArcSight data fields. Microsoft Windows 2012/Windows 8 events are supported.

The *ArcSight SmartConnector Mappings to Windows Security Events* document provides the main mappings for the Windows Event Log SmartConnectors; the field mappings listed in this document are specifically for the SmartConnector for Windows Event Log – Unified: Microsoft WINS Server.

### Product Overview

Microsoft WINS servers are designed to prevent the administrative difficulties that are inherent in the use of both IP broadcasts and static mapping files such as LMHOSTS files. Microsoft WINS is designed to eliminate the need for IP broadcasts (which use valuable network bandwidth and cannot be used in routed networks), while providing a dynamic, distributed database that maintains computer name-to-IP-address mappings.

WINS servers use a replicated database that contains NetBIOS computer names and IP address mappings (database records). When Windows-based computers log on to the network, their computer name and IP address mapping are added (registered) to the WINS server database, providing support for dynamic updates. The WINS server database is replicated among multiple WINS servers in a LAN or WAN. One of the benefits of this database design is that it prevents different users from registering duplicate NetBIOS computer names on the network.

WINS clients, referred to as WINS-enabled clients, are configured to use the services of a WINS server. Windows NT-based clients are configured with the IP address of one or more WINS servers by using the WINS Address tab on the Microsoft TCP/IP Properties page in **Control Panel -> Network**.

### WINS Configuration

You can run the Registry Editor program at the command prompt to configure a WINS server by changing the values of the Registry parameters. Parameters for logging include:

Configuration Option	Description
Logging Enabled	Specifies whether logging of database changes to J50.log files should be turned on.
Log Detailed Events	Specifies whether logging events is verbose mode. (This requires considerable computer resources and should be turned off if you are tuning for performance.)

### Connector Installation and Configuration

Follow the installation and configuration procedures in the [SmartConnector Configuration Guide for Microsoft Windows Event Log – Unified](#), selecting **Microsoft Windows Event Log – Unified** as the connector to be configured. During installation, select **true** for the **System Logs** field for system events to be collected.

## Collect Events from the Application or System Event Log

When collecting events from System Event logs (such as NTServicePack, Service Control Manager, WINS), select **System** for Windows Log type.

When collecting events from application event logs (such as Microsoft Forefront Protection 2010 for Exchange, Microsoft SQL Server Audit), select **Application** for Windows Log type.

To collect events from the event logs, set the host parameter **eventlogtypes** as follows:

```
eventlogtypes=application,system
```

Access the connectors advanced parameters to specify the event log types:

- 1 From the `$ARCSIGHT_HOME\current\bin` directory in a DOS command window enter:
 

```
arcsight connectorsetup
```
- 2 When asked whether you want to enter Wizard mode, click **No**.
- 3 The window for the Agent Configuration Tool is displayed. From the **Options** menu, select **Show Internal Parameters**. The advanced configuration parameters for the connector are displayed.
- 4 Locate the **eventlogtypes** parameter; the initial value is null. Enter the appropriate event log names.

For more information about application and system event support, see the *SmartConnector Configuration Guide for Microsoft Windows Event Log – Unified*.

## Windows 2012/Windows 8

### General

ArcSight Field	Vendor Field
Device Vendor	'Microsoft'
Device Product	'Microsoft Windows'
Device Custom String 4	Reason or Error Code

### 4097

ArcSight Field	Vendor Field
Name	'WINS initialized properly and is now fully operational'

### 4098

ArcSight Field	Vendor Field
Name	'WINS was terminated by the service controller'
Message	'WINS will gracefully terminate'

**4143**

ArcSight Field	Vendor Field
Name	'WINS scavenged its records in the WINS database'
Message	'The number of records scavenged is given in the data section'

**4178**

ArcSight Field	Vendor Field
Name	'The WINS Pull configuration key could not be created or opened'
Message	'Check to see if the permissions on the key are set properly, system resources are low, or the registry is having a problem'

**4179**

ArcSight Field	Vendor Field
Name	'The WINS Push configuration key could not be created or opened'
Message	'Check to see if the permissions on the key are set properly, system resources are low, or the registry is having a problem'

**4180**

ArcSight Field	Vendor Field
Name	'The WINS\\Parameters key could not be created or opened'
Message	'Check to see if the permissions on the key are set properly, system resources are low, or the registry is having a problem'

**4224**

ArcSight Field	Vendor Field
Name	'WINS encountered a database error'
Message	'This may or may not be a serious error. WINS will try to recover from it'

**4318**

ArcSight Field	Vendor Field
Name	'WINS could not start due to a missing or corrupt database'
Message	'Restore the database using WINS Manager (or winscl.exe found in the Windows 2000 Resource Kit) and restart WINS'

**4329**

ArcSight Field	Vendor Field
Name	'The WINS server has started a scavenging operation'

**4330**

ArcSight Field	Vendor Field
Name	'The WINS server has completed the scavenging operation'

**5001**

ArcSight Field	Vendor Field
Name	'WINS is scavenging the locally owned records from the database'
Message	'The version number range that is scavenged is given in the data section, in the second to fifth words, in the order: from_version_number (low word, high word) to_version_number (low word, high word)'

**5002**

ArcSight Field	Vendor Field
Name	'WINS is scavenging a chunk on N records in the version number range from X to Y'
Message	'N, X and Y (low word, high word for version numbers) are given in the second to sixth words in the data section'

**4181**

ArcSight Field	Vendor Field
Name	'The subkey could not be created or opened'
Message	'This key should be there if you want WINS to do consistency checks on its database periodically. NOTE: Consistency checks have the potential of consuming large mounts of network bandwidth. Check to see if the permissions on the key are set properly, system resources are low, or the registry is having a problem'

**4252**

ArcSight Field	Vendor Field
Name	'WINS did not find any subkeys under the Pull key'

**4253**

ArcSight Field	Vendor Field
Name	'WINS did not find any subkeys under the Push key'

**4309**

ArcSight Field	Vendor Field
Name	'System Resource Information'
Device Custom Number 1	Processor Count
Device Custom Number 2	Physical Memory
Device Custom Number 3	Memory available for allocation

**4325**

ArcSight Field	Vendor Field
Name	'WINS could not read the Initial Challenge Retry Interval from the registry'

### 4326

ArcSight Field	Vendor Field
Name	'WINS could not read the Challenge Maximum Number of Retries from the registry'

### 4119

ArcSight Field	Vendor Field
Name	'WINS received a packet that has the wrong format'

### 4337

ArcSight Field	Vendor Field
Name	'WINS Server could not initialize security to allow the read-only operations'